

RoHS

Reach

Explanation of PN.

**2002J H XX - 3 XX**

① ② ③ ④ ⑤

- ① Series No.
- ② Connector Type : Housing
- ③ Circuits No.
- ④ Insulator Material : Nylon66, UL 94-V0
- ⑤ Color : WH : White  
BK : Black

Specification :

Current Rating : 2A AC,DC

Voltage Rating : 125V AC,DC

Temperature Range : -25°C ~ +85°C

Contact Resistance : 20mΩ Max.


Insulation Resistance : 1000mΩ Min.


Withstanding Voltage : 800V AC/minute

Insulator Material : Nylon66, UL 94-V0

## Ordering Information &amp; Dimension

Circuit No.	Dimensions	
	A	B
02P	2.00	4.90
03P	4.00	6.90
04P	6.00	8.90
05P	8.00	10.90
06P	10.00	12.90
07P	12.00	14.90
08P	14.00	16.90
09P	16.00	18.90
10P	18.00	20.90
11P	20.00	22.90
12P	22.00	24.90
13P	24.00	26.90
14P	26.00	28.90
15P	28.00	30.90



	<b>DESCRIPTION :</b> <b>2.00mm Pitch,</b> <b>Housing, Single Row</b>	<b>GENERAL TOLERANCE</b>	
	<b>PART NO. :</b> <b>2002JHXX-3XX</b>	X.X ± 0.25 X.XX ± 0.15 X.XXX ± 0.05	SCALE : Free 