

RoHS

Reach

Explanation of PN.

3030J V X S D XX - 6 BK 0

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series No.
- ② Connector Type : Straight Angle
- ③ Foot Length : F1 : X=2.00mm
F2 : X=3.20mm
- ④ Mounting Type : SMD Type
- ⑤ Row Type : Dual Row
- ⑥ Circuits No.
- ⑦ Insulator Material : 6 : LCP, UL 94-V0
- ⑧ Color : BK : Black
- ⑨ Contact Plating : Tin-plated


Specification :

Current Rating :	5A AC,DC
Voltage Rating :	250V AC,DC
Temperature Range :	-25°C ~ +85°C
Contact Resistance :	10mΩ Max.
Insulation Resistance :	1000mΩ Min.
Withstanding Voltage :	1500V AC/minute
Pin Material :	Brass
Insulator Material :	LCP, UL 94-V0

Ordering Information & Dimension

PART NO.	Dimensions		PART NO.	Dimensions	
	A	B		A	B
02	3.00	9.65	08	21.00	27.65
03	6.00	12.65	09	24.00	30.65
04	9.00	15.65	10	27.00	33.65
05	12.00	18.65	11	30.00	36.65
06	15.00	21.65	12	33.00	39.65
07	18.00	24.65			

PCB Layout

	DESCRIPTION : 3.00mm Pitch, Receptacle, Dual Row, SMD, Straight Angle, With Foot	GENERAL TOLERANCE	
	PART NO. : 3030JVXSDXX-6BK0	X.X ± 0.25 X.XX ± 0.15 X.XXX ± 0.05	SCALE : Free 